



Data Loggers Real Time Telemetry



Eigenschappen

- Small, leadless logger (8.3mm x 25.4mm)
- Wireless transmission (telemetry) and logging of data
- · Data stored in memory
- Automatic measurements
- Simple and cost effective
- · Group and unconfined housing

Description

The heart rate sensors DST...RF-HRT simultaneously measure long term heart rate and core temperature in animals. This makes them ideal for studies in which baseline and immunology responses are recorded, they are also suitable for toxicological, metabolic and thermoregulation studies. The heart rate is derived from a leadless single channel ECG in which the electrodes are part of the housing material, making the logger especially easy to implant. The logger then takes a burst measurement on any set time interval and calculates the mean heart rate for each recording. For validation purposes, each individual burst is graded with a certain quality index (QI) accessible in the accompanying application software.

Easy to use and reuseable

The heart rate sensor is simple in use, from setup and surgery to data transmission and retrival. DST ...RF-HRT logger is easy to sterilize (gas sterilizer or 70% ethanol) and can be reused as long as the batteries last, which makes the logger very cost efficient. Each DST ...RF-HRT has its own five digit serial number permanently marked on the logger housing as well as placed in the logger's memory and provided with all downloaded data. DSTRF-HRT is especially useful when you wish to record a comprehensive data set throughout your research with no disturbance to the animal or subject. Each logger comes with a calibration certificate.

Easy to use and reuseable

The telemetry system consists of seven components: DST... RF-HRT telemetry data logger with a heart rate and temperature sensor, a RF box transreceiver module placed on each cage, an antenna placed on each cage, a Personal Area Network (PAN) controller which is the receiving module connected to a computer, Communication Box which serves as an interface between the logger and the PC, and Mercury and Gná application software. The DST microRF-HRT is based on our DST micro-HRT and gives the users the benefit of both continuous logging and telemetry. The logger can be programmed to record temperature as often as once per minute. It will store those data points in its memory and transmit the data to Gná, our online user software, as often as required by the researcher. The







measurement data can be analysed in graphic and tabular form and exported to most statistical analysis programs. The software also provides the user with some basic statistic information on the data such as minimum and maximum values on defined area, median, average, distribution of values etc.

The Telemetry System

The telemetry system consists of seven components: DST ...RF-HRT telemetry data logger with a heart rate and temperature sensor, a RF box transreceiver module placed on each cage, an antenna placed on each cage, a Personal Area Network (PAN) controller which is the receiving module connected to a computer, Communication Box which serves as an interface between the logger and the PC, and Mercury and Gná application software. The DST microRF-HRT is based on our DST micro-HRT and gives the users the benefit of both continuous logging and telemetry. The logger can be programmed to record temperature as often as once per minute. It will store those data points in its memory and transmit the data to Gná, our online user software, as often as required by the researcher. The measurement data can be analysed in graphic and tabular form and exported to most statistical analysis programs. The software also provides the user with some basic statistic information on the data such as minimum and maximum values on defined area, median, average, distribution of values etc.



Each telemetry system needs to have a PAN to receive the data from the RF boxes. It is connected to the computer using a serial cable and a USB converter. How far the PAN can be placed away from the RF box varies greatly on the configuration of the lab but in most cases it will transmit about 20-30 meters.



Specificaties

DST logger specs	DST NanoRF-T	DST MicroRF-T	DST MicroRF-HRT
Sensors	Temperature	Temperature	Temperature
Size: Ø x lenght	6 x 17,5 mm	8,3 x 25,4 mm	8,3 x 25,4 mm
Weight	1,3 g	3,3 g	3,3 g
Battery Life	12 months*	21 months*	2,5 months*



Memory Type	Non-volatile EE-PROM	Non-volatile EE-PROM	Non-volatile EE-PROM
Memory capacity	43476 measurements	43476 measurements	43690 measurements
Data resolution	12 bits	12 bits	12 bits
Min. measuring interval	1 min	1 min	1 min
Temperature range	5°C to 45°C	5°C to 45°C	5°C to 45°C
Temperature resolution	0,032°C	0,032°C	0,032°C
Temperature accuracy	+/- 0,2°C	+/- 0,2°C	+/-0,2°C
HR sampling Frequency	NA	NA	100-800Hz
Telemetry RF Frequency	500 kHz	500 kHz	500 kHz
Transmissinon range to RF box.	20-30 cm	20-30 cm	20-30 cm

PAN, receiver

Size	85 x 75 x 25 mm
Total number of RF boxes per PAN	64
Total number of loggers per PAN	640
PAN communication protocol	MiWi
Channels	16, software determined
Power supply for PAN	12VDC
Software required	Gná

RF box, Transceiver

Size	85 x 75 x 25 mm
Transmission range to PAN	20-30 meters ***
Transmission frequency	2,4 GHz
Battery Life	up to 3 weeks, rechargable
Recharge Time	3-4 hours
Number of loggers per RF box	1-10
Antenna	Placed under the cage***









- * For a sampling interval of 10min
- **Range may vary depending on laboratory configuration
- ***Antenna can be made in another shape for other placement

Bestelnummer

180000095	DST microRF-T Temperature recorder
180000096	DST nanoRF-T Temperature recorder
180000097	DST microRF-HRT Heart rate and temperature recorder
	Telemetry Accesories
180000091	communication box
180000099	Antenna, 1 per cage needed
180000100	RF Box Data receiver 1 per cage needed
180000101	PAN receiving Module, on eper PC
180000102	Mercury & GNA Software